



(43) International Publication Date 1 July 2004 (01.07.2004)

International Bureau

PCT

(10) International Publication Number WO 2004/055716 A1

(51) International Patent Classification7: G07C 9/00, H04N 7/18

G06K 9/00,

al.; Patentwerk B.V., P.O. Box 1514, NL-5200 BN 's-Her-

(21) International Application Number:

PCT/NL2003/000839

(22) International Filing Date: 28 November 2003 (28.11.2003)

(25) Filing Language:

Dutch

(26) Publication Language:

English

(30) Priority Data:

1022036

29 November 2002 (29.11.2002) NL

(71) Applicant (for all designated States except US): VCS IN-TERNATIONAL B.V. [NL/NL]; Havenweg 28, NL-5145 NJ Waalwijk (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): VAN DELJZEN,

Wilhelmus, Petrus, Arnoldus [NL/NL]; Hobbestraat 7, NL-5143 GT Waalwijk (NL).


(74) Agents: VAN DEN HEUVEL, Henricus, Theodorus et

togenbosch (NL).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SYSTEM FOR PROCESSING VISUAL INFORMATION AND METHOD OF VISUAL SURVEILLANCE



(57) Abstract: The invention relates to a system for processing visual information, comprising: a number of cameras for recording visual information, a control room in communication with the cameras and having means for displaying recorded visual information, and control means for influencing the information displayed in the control room. The invention also relates to a method for visual surveillance.








Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG,
- CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



10

15

20

25 .

30






SYSTEM FOR PROCESSING VISUAL INFORMATION AND METHOD OF VISUAL SURVEILLANCE

The invention relates to a system for processing visual information, comprising: a number of cameras for recording visual information, a control room in communication with the cameras and having means for displaying recorded visual information, and control means for influencing the information displayed in the control room. The invention also relates to a method of visual surveillance.

The application of cameras for recording visual information is generally known. The use of camera surveillance has expanded enormously in recent times in order to allay a sense of insecurity and to increase safety. Use is generally made for this purpose of a number of different cameras, the images from which are transmitted to a central communications room. In the communications room the operator (security guard) normally views some of the provided images. Such systems are applied in city centres, industrial estates, stadiums and so on. The investment for setting up and keeping said camera systems operational is very considerable. It is necessary to take into consideration here infrastructural investment (cameras, connections, processing equipment) and staff (salary costs, training courses). The improvements in existing systems are sought in the prior art mainly in the improvement in the infrastructural means. However, applicant has had as insight that a very significant limitation of the existing systems is rather to be found in the "human factor".

The invention therefore has for its object to provide an improved system for processing visual information and to a method of visual monitoring with which particularly the behaviour of an operator of a surveillance system can be improved.

The invention provides for this purpose a system for processing visual information, comprising: a number of cameras for recording visual information, a control room in communication with the cameras and having means for displaying recorded visual information, and control means for influencing the information displayed in the control room, characterized in that the system is also provided with storage means for storing the operations performed with the control means. The storage means are preferably also adapted to store the operations performed with the control means in combination with at least a part of the visual information displayed as a result of the operations performed



10

15

20[.]





with the control means. With such a system the behaviour of an operator also falls within the system limits. The behaviour of the operator hereby becomes measurable and thus more controllable. Now that the behaviour of the operator can also be measured. and evaluated, there is the possibility of tracing, and then influencing, less favourable behaviour of operators. Owing to the possibility of monitoring the behaviour of an operator, incorrect behaviour of an operator can also be dealt with specifically. It is expected that providing the possibility of supervision of the behaviour of an operator will already have a favourable effect on behaviour. Linked storage of the displayed visual information and storage of the performed operations provides an easier coupling of operations and the images displayed as a consequence thereof. Also from a legal point of view this has the advantage that the behaviour of an operator can thus be analysed more easily. In particular circumstances it is customary that all observed visual information is stored (for instance on hard disks or tapes). The access to such records (partly because of privacy laws and the enormous quantity of records) is however often impossible or at least extremely time-consuming. This problem does not exist in the system according to the present invention.

In an advantageous embodiment variant of the system, the control room is also provided with communication means and the storage means are adapted to store the operations performed with the communication means. The communication behaviour of an operator (for instance an emergency switch, a telephone line and so on) is thus also brought within the controllable system limits. The communication behaviour of operators can hereby also be evaluated and, in general, improved.

- In order to link the identity of an operator in simple manner to the stored operations performed with the control means, it is recommended that the system is also provided with input means for supplying to the storage means an identification of the operator of the control means.
- 30 For a simple further processing of the information supplied to the storage means, it is advantageous if the system is also provided with a data processing unit with which statistical information is generated from the operations performed with the control means. Such statistical information can thus be generated in real time, so that a rapid feedback is also possible. The feedback can be automated when the data processing unit



15

. 20

25

30





connects to a control module with which the information displayed in the control room is controlled. It is possible here to envisage activation (display of an image recorded ... with a specific camera) if this image has not been displayed for a longer period, or expressly displaying, on the basis of historical information, a camera image which has 5 previously prompted a particular intervention (such as displaying the image of a street in an entertainment district on Saturday evening around closing time because this has resulted in police assistance of a determined high priority being called in a number of times earlier in the month). Another possibility is to cause an alarm signal to go off (for instance a light signal and/or an acoustic signal) in the control room when an operator has not performed any operations for a determined period. The system is preferably also provided with second storage means adapted to store the statistical information generated by means of the data processing unit. This information can also be recorded therewith. A further development of the system even makes it possible to monitor the behaviour of an operator of the system by means of detection means arranged for this purpose in the control room.

The invention also provides a method of visual surveillance, comprising the steps of: A) recording visual information by means of a number of cameras, B) feeding the recorded information to a control room, C) selecting by an operator for observation purposes of a part of the available information from the recorded information fed to the control room, D) storing the information selected by the operator. In a preferred application of the method, the information selected by the operator as according to processing step (D) is stored in relation to the selection behaviour applied for this purpose by the operator. From the selection behaviour can then be generated statistical information which can be used to actively influence the operator. Such a method provides the advantages as already described above with reference to the device according to the present invention.

The control room for processing information recorded by the system can also be supplied with personal identification data. Such personal identification data can be generated by linking visual information to another information source. Such a source can for instance be a file which comes from an investigative department (linking outward appearance to an identification). Conversely, it is also possible to generate this information with the system. A stadium for instance can thus be provided with a camera which is disposed close to an entrance to the stadium and which is connected to the

control room, in addition to a read device which is disposed close to an entrance to the stadium for reading a personal identification and which is connected to the control room. This provision increases the possibilities in respect of identifying people in the stadium. The linking of data can thus be made use of later when it is desired to obtain further information relating to the identity of a person observed in the complex by the camera device. It thus becomes possible to maintain order with greater efficiency (and to take preventive measures for future events) in a complex where large numbers of people are present. It is noted in respect of all (statistical) information generated by the system that this information is also highly suitable for supporting policy-related decision-making processes.

The present invention will be further elucidated on the basis of the non-limitative embodiments shown in the following figures, wherein:

figure 1 shows a schematic view of a surveillance system according to the present invention,

figure 2 shows a schematic view of an alternative embodiment variant of a surveillance system according to the present invention, and figure 3 is a schematic view of a part of a second alternative embodiment variant of a

surveillance system according to the present invention.

20

25

30


10

15

Figure 1 shows a surveillance system 1 provided with a number of cameras 2 which lead with cables 3 to a control room 4. In control room 4 the cables 3 connect to control means 5, provided schematically here with buttons 6. An observer 7 (also referred to as an operator) can determine by means of buttons 6 from which cameras 2 the images are displayed on observation monitors 8. The observation behaviour of observer 7 determines in significant part the quality of the surveillance services. This behaviour is stored in a database 9 in addition to the data relating to which buttons 6 have been operated at which moment and in which way by observer 7, and it is advantageous if the images displayed on monitors 8 as a result of these operations are also stored in database 9.

Figure 2 shows an alternative embodiment variant of a surveillance system 10 with a number of cameras 11 which are connected with cables 12 to a control panel 13.

Depending on the choices made during use of control panel 13, images from several of







the cameras 11 are shown on monitors 14 in selected manner (for instance zoomed-in to a greater or lesser extent). The information relating to the displayed images is also transmitted to a database 15 where it is stored. Another information flow relating to the selected images goes to a computer 16. Computer 16 processes the information flow in respect of the selected images into statistical information which is then displayed (for instance in real time) in a window 17 on monitors 14. The statistical information coming from computer 16 is also fed to database 15 for storage thereof. It is noted that the information flows as shown relate only to a randomly chosen variant. There are numerous ways of routing the information flows which are likewise possible.

Finally, figure 3 shows a part of a second embodiment variant of a surveillance system 20 in which, in addition to a control panel 22 and monitors 23, a camera 24 is also disposed in a control room 22 with which an operator 25 is observed. The information coming from camera 24 is fed for storage thereof to a database 26 in which are also stored the data relating to use of control panel 22 and the images selected as a result thereof.







Claims

15

20

25

30

- 1. System (1, 10, 20) for processing visual information, comprising:
- a number of cameras (2, 11) for recording visual information,
- a control room (4, 21) in communication with the cameras (2, 11) and having means (8, 14, 23) for displaying recorded visual information, and
 - control means (5, 6, 13, 22) for influencing the information displayed in the control room (4, 21),
- characterized in that the system (1, 10, 20) is also provided with storage means (9, 15, 26) for storing the operations performed with the control means (5, 6, 13, 22).
 - 2. System (1, 10, 20) as claimed in claim 1, characterized in that the storage means (9, 15, 26) are adapted to store the operations performed with the control means (5, 6, 13, 22) in combination with at least a part of the visual information displayed as a result of the operations performed with the control means (5, 6, 13, 22).
 - 3. System (1, 10, 20) as claimed in claim 1 or 2, characterized in that the control room (4, 21) is also provided with communication means and that the storage means (9, 15, 26) are adapted to store the operations performed with the communication means.
 - 4. System (1, 10, 20) as claimed in any of the foregoing claims, characterized in that the system (1, 10, 20) is also provided with input means (24) for supplying to the storage means (9, 15, 26) an identification of an operator (7, 25) of the control means (5, 6, 13, 22).
 - 5. System (1, 10, 20) as claimed in any of the foregoing claims, characterized in that the system (1, 10, 20) is also provided with a data processing unit (16) with which statistical information is generated from the operations performed with the control means (5, 6, 13, 22).
 - 6. System (1, 10, 20) as claimed in claim 5, characterized in that the system (1, 10, 20) is also provided with second storage means (26) adapted to store the statistical information generated by means of the data processing unit.







- 7. System (1, 10, 20) as claimed in claim 5 or 6, characterized in that the data processing unit (16) connects to a control module with which the information displayed in the control room (4, 21) is transmitted.
- 5 8. System (1, 10, 20) as claimed in any of the foregoing claims, characterized in that the system (1, 10, 20) is also provided with detection means (24) for observing behaviour of an operator (7, 25) of the system (1, 10, 20).
- 9. System (1, 10, 20) as claimed in claim 8, characterized in that the detection means (24) connect to the storage means (9, 15, 26) for storing the operations performed with the control means (5, 6, 13, 22), which storage means (9, 15, 26) are also adapted to store the information generated with the detection means (24).
 - 10. Method of visual surveillance, comprising the steps of:
- 15 A) recording visual information by means of a number of cameras (2, 11),
 - B) feeding the recorded information to a control room (4, 21),
 - C) selecting by an operator (7, 25) for observation purposes of a part of the available information from the recorded information fed to the control room (4, 21), and
 - D) storing the information selected by the operator (7, 25).

- 11. Method as claimed in claim 10, characterized in that the information selected by the operator (7, 25) as according to processing step (D) is stored in relation to the selection behaviour applied for this purpose by the operator (7, 25).
- 25 12. Method as claimed in claim 10 or 11, characterized in that statistical information is generated from the selection behaviour.
 - 13. Method as claimed in claim 12, characterized in that the statistical information is used to actively influence the operator (7, 25).

30

14. Method as claimed in any of the claims 10-13, characterized in that the control room (4, 21) for processing information recorded by the system (1, 10, 20) can also be supplied with personal identification data.



15. Method as claimed in claim 14, characterized in that the personal identification data are generated by linking visual information to another information source.






FIG. 1




FIG. 2








FIG. 3

ication No PCT/N=03/00839

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 G06K9/00 G070 G07C9/00 H04N7/18 According to International Patent Classification (IPC) or to both national classification and IPC Minimum documentation searched (classification system followed by classification symbols) IPC 7-606K-607C-H04NDocumentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal C. DOCUMENTS CONSIDERED TO BE RELEVANT Relevant to claim No. Category ° Citation of document, with indication, where appropriate, of the relevant passages 1-3,10,X WO 97 40624 A (SENSORMATIC ELECTRONICS CORP) 30 October 1997 (1997-10-30) page 9, line 1 -page 11, line 26 page 13, line 35 -page 17, line 2 figures 2,5 1 - 15Α WO 98 25229 A (INGRAM DARRYL ; COFFIN JEFFREY S (US); TECHNOLOGY RECOGNITION SYSTE) 11 June 1998 (1998-06-11) page 6, line 5 -page 8, line 3 page 10, line 33 -page 13, line 24 WO 02 48971 A (KONINKL PHILIPS ELECTRONICS 1,2,6, Α 10,14,15 NV) 20 June 2002 (2002-06-20) the whole document Patent family members are listed in annex. Further documents are listed in the continuation of box C. Special categories of cited documents: later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the "A" document defining the general state of the art which is not considered to be of particular relevance invention *E* earlier document but published on or after the international "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such docu-"O" document referring to an oral disclosure, use, exhibition or ments, such combination being obvious to a person skilled other means document published prior to the international filing date but later than the priority date claimed in the art. "&" document member of the same patent family Date of mailing of the international search report Date of the actual completion of the international search 15/03/2004 5 March 2004 Authorized officer Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016 Van der Zaal, R

INTERNATION GEARCH REPORT

Internation logication No PCT/N= 03/00839

Patent document dted in search report		Publication date		Patent family member(s)	Publication date
WO 9740624	A	30-10-1997	US AU AU BR CA EP JP WO	5982418 A 724687 B2 3056097 A 9708732 A 2250280 A1 0898840 A1 2000513517 T 9740624 A1	09-11-1999 28-09-2000 12-11-1997 03-08-1999 30-10-1997 03-03-1999 10-10-2000 30-10-1997
WO 9825229	Α	11-06-1998	US AU WO	5991429 A 5463598 A 9825229 A1	23-11-1999 29-06-1998 11-06-1998
WO 0248971	Α	20-06-2002	US CN WO EP	2002071033 A1 1423804 T 0248971 A2 1346327 A2	13-06-2002 11-06-2003 20-06-2002 24-09-2003